

# JCPT(RT)

## Self-Propelled Rough-Terrain Scissor Lifts




### Standard Equipment

- Proportional Controls
- Self-lock Gate On Platform
- 4WD
- Self-leveling Hydraulic Outriggers
- Automatic Brake System
- Cylinder Holding Valve
- Onboard Diagnostic System
- Tilt Sensor With Alarm
- All Motion Alarm
- Horn
- Hour Meter
- Safety Brackets
- Folding Guardrails
- Automatic Single Roll Out Deck
- Flashing Beacon
- Slide-out Engine Tray
- Emergency Stop Button
- Anti-restart Engine Protection
- European III Emission Engine
- Hydraulic Oil Cooler
- Vertical Style Lift Gate

### Options

- Overload Sensor With Alarm
- AC power On The Platform
- Hydraulic Generator
- Hydraulic Welder
- Hydraulic Compressor
- Hydraulic Water Pump
- Platform Work Lights
- Non Marking Tyre



DINGLI JCPT2223RT	
S.W.L	750kg
S.W.L On Extension	500kg
Max Occupants	4
A Max. Working Height	22.00m
B Max. Platform Floor Height	20.00m
C Overall Length	4.80m
D Overall Width	2.27m
Overall Height(Rails Up)	3.68m
E Overall Height(Rails Down)	2.84m
Platform Size(Length/Width)	4.35m×1.85m
F Platform Extension Size	2.00m
Ground Clearance	0.22m
Wheelbase	3.13m
Turning Radius(Inside/Outside)	2.15m/5.35m
Engine	Kubota v2403-M-DI 36.5kW/2600rpm
Travel Speed(Stowed)	6.0km/h
Travel Speed(Raised)	0.7km/h
Up/Down Speed	75/60sec
Gradeability	30%
Max. Working Slope	2°/3°
Hydraulic Tank	160L
Diesel Tank	90L
Tyres	30×12-20
Weight	12040kg



Automatic Leveling Outriggers



Flashing Beacon



Emergency Lowering System



Gradeability



Extended Platform



Folding Guardrails



Swing-out Engine Tray



Safety Bracket